





# PRODUCT CONFORMITY CERTIFICATE

This is to certify that the

# ACF5000 measuring system

Manufactured by:

# ABB Automation GmbH

Stierstädter Strasse 5 60488 Frankfurt am Main Germany

has been assessed by CSA Group and for the conditions stated on this certificate complies with:

# **Environment Agency Guidance**

"MCERTS for stack emissions monitoring equipment at industrial installations"
- Continuous emissions monitoring systems(CEMS)
Published 20 October 2020

EN 15267-1:2009, EN15267-2:2009, EN 15267-3:2007

& QAL 1 as defined in EN 14181: 2014

### Certification ranges:

CO	$0-75~(0-300,0-4000)~mg/m^3$	$NH_3$	$0 - 5 (0 - 15, 0 - 230) \text{ mg/m}^3$
NO	$0-150 \; (0-400,  0-2000) \; mg/m^3$	H <sub>2</sub> O	0 – 40 Vol%
$NO_2$	$0-80 \; (0-600,  0-1000) \; mg/m^3$	CO <sub>2</sub>	0 – 30 Vol%
$N_2O$	$0 - 50 (0 - 1000) \text{ mg/m}^3$	H <sub>2</sub> CO	$0 - 20 \text{ mg/m}^3$
SO <sub>2</sub>	$0-75~(0-300,0-5000)~mg/m^3$	CH <sub>4</sub>	0 - 7.5 (0 – 200) mg/m <sup>3</sup>
HCI	$0-15~(0-90,0-2000)~mg/m^3$	Total C (FID)	$0-15\ (0-30, 0-300, 0-500)\ mg/m^3$
HF	$0 - 3 (0 - 6, 0 - 300) \text{ mg/m}^3$	$O_2$ (Zr $O_2$ )	0 – 25 Vol%

Project No.: 80108227

Certificate No: Sira MC160309/05
Initial Certification: 19 August 2016
This Certificate issued: 23 December 2021
Renewal Date: 18 March 2026

MCERTS is operated on behalf of the Environment Agency by

1.5.7

Andrew Young

Environmental Team Manager

# CSA Group Testing UK Ltd



Unit 6, Hawarden Industrial Park Hawarden, Deeside, CH5 3US Tel: +44 (0)1244 670 900

The MCERTS certificate consists of this document in its entirety.
For conditions of use, please consider all the information within.
This certificate may only be reproduced in its entirety and without change
To authenticate the validity of this certificate please visit www.csagroupuk.org/mcerts







#### **Certificate Contents**

Approved Site Application	2
Basis of Certification	
Product Certified	
Certified Performance	4
Description	18
General Notes	18

### **Approved Site Application**

Any potential user should ensure, in consultation with the manufacturer, that the monitoring system is suitable for the intended application. For general guidance on monitoring techniques refer to the Environment Agency Monitoring Technical Guidance Notes available at <a href="https://www.mcerts.net">www.mcerts.net</a>

This instrument is considered suitable for use on waste incineration and large combustion plants. This CEMS has been proven suitable for its measuring task (parameter and composition of the flue gas) by use of the QAL 1 procedure specified in EN14181. The lowest certified range for each determinand shall not be more than 1.5 times the daily average emission limit value (ELV) for incineration plants, and not more than 2.5 times the ELV for other types of applications.

#### **Basis of Certification**

This certification is based on the following Test Report(s) and on Sira's assessment and ongoing surveillance of the product and the manufacturing process:

TÜV Rheinland Report 936/21219814/A dated 6th April 2016

TÜV Rheinland Report 936/21219814/C dated 24th January 2017

TÜV Rheinland Report 936/21219814/G dated 8th October 2018







### **Product Certified**

The ACF5000 measuring system consists of the following parts:

1. Sample Probe	2. Heated Filter	3. Heated	4. Gas	5. Analyser
		Sample Line	Conditioning	
Model:	Model:	Model:	Model:	Model:
ABB Type 40	ABB PFE2 filter	Heated ABB	ASP-block	ACF5000 Analyser
(screw mounted)		TBL01-S sampling	(integrated)	cabinet with:
or Type 42		line (180°C) with		<ul> <li>Interferometer</li> </ul>
(flange-mounted)		an inner diameter		· FID
probe tube		of 6mm, made of		· O <sub>2</sub> Sensor
		teflon, max 60m		· Air improvement
		long		· Cooling unit (for
				use at 5 – 45 °C,
				or fan for use at 5
				– 30 °C)

# Allowable variations could include:

- A different brand or model of sampling system of the same type, provided that there is evidence the alternative system works with similar types of CEM.
- Additional manifolds and heated valves used to allow more than one analyser to share a sampling system.

This certificate applies to all instruments fitted with software version 5.2.16 (Syscon), 3.5.99 (AMC), and serial number 3.351922.3 onwards.







#### **Certified Performance**

The instrument was evaluated for use under the following conditions:

Ambient Temperature Range: +5°C to +45°C

Instrument IP rating: IP54

Note: For outdoor installations the analyser needs to be mounted into an IP65 environment. If the instrument is supplied with an enclosure, then the ambient temperature shall be monitored inside the enclosure to ensure that it stays within the above ambient temperature range. The CEM is nominally equipped with an air-conditioning unit and testing took place in the temperature range between 5°C and 45°C. Additionally, the CEM may be used with a fan instead of an air-conditioning unit, in the temperature range between 5°C and 30°C.

Results are expressed as error % of certification range, unless otherwise stated.

	Test	Results expressed as % of the certification range		6 of the	Other results	MCERTS specification	
		<0.5	<1	<2	<5		
Response time							
$O_2$	(0-25%Vol)					37s	<200s
CO	(0-75mg/m <sup>3</sup> )					185s	<200s
CO	(0-300 mg/m <sup>3</sup> )					136s	<200s
CO	(0-4000 mg/m <sup>3</sup> )					127s	<200s
NO	(0-150 mg/m <sup>3</sup> )					134s	<200s
NO	(0-400 mg/m <sup>3</sup> )					178s	<200s
NO	(0-2000 mg/m <sup>3</sup> )					128s	<200s
$NO_2$	(0-80 mg/m <sup>3</sup> )					172s	<200s
$NO_2$	(0-600 mg/m <sup>3</sup> )					137s	<200s
NO <sub>2</sub>	(0-1000 mg/m <sup>3</sup> )					164s	<200s
N <sub>2</sub> O	(0-50 mg/m <sup>3</sup> )					158s	<200s
N <sub>2</sub> O	(0-1000 mg/m <sup>3</sup> )					129s	<200s
SO <sub>2</sub>	(0-75 mg/m <sup>3</sup> )					186s	<200s
SO <sub>2</sub>	(0-300 mg/m <sup>3</sup> )					168s	<200s
SO <sub>2</sub>	(0-300 mg/m <sup>3</sup> )					135s	<200s
HCI	(0-15 mg/m <sup>3</sup> )					278s	<400s
HCI	(0-90 mg/m <sup>3</sup> )					150s	<400s
HCI	(0-2000 mg/m <sup>3</sup> )					154s	<400s
HF	(0-3 mg/m <sup>3</sup> )					198s	<400s
HF	(0-6 mg/m <sup>3</sup> )					187s	<400s
HF	(0-300 mg/m <sup>3</sup> )					163s	<400s
$NH_3$	(0-5 mg/m <sup>3</sup> )					170s	<400s







	Test	Results expressed as % of the certification range		Other results	MCERTS specification		
		<0.5	<1	<2	<5		
NH₃	(0-15 mg/m <sup>3</sup> )					172s	<400s
NH <sub>3</sub>	(0-230 mg/m <sup>3</sup> )					158s	<400s
H <sub>2</sub> O	(0-40%Vol)					137s	<200s
CO <sub>2</sub>	(0-30%Vol)					139s	<200s
H₂CO	(0-20 mg/m <sup>3</sup> )					127s	<200s
CH₄	(0-7.5 mg/m <sup>3</sup> )					192s	<200s
CH <sub>4</sub>	(0-200 mg/m <sup>3</sup> )					133s	<200s
TOC	(0-15 mg/m <sup>3</sup> )					49s	<200s
TOC	(0-30 mg/m <sup>3</sup> )					50s	<200s
TOC	(0-300 mg/m <sup>3</sup> )					45s	<200s
TOC	(0-500 mg/m <sup>3</sup> )					49s	<200s
Repeatability sta	andard deviation at zero						
O <sub>2</sub>		0.0					<0.2%
CO		0.0					<2.0%
NO		0.1					<2.0%
NO <sub>2</sub>		0.3					<2.0%
N <sub>2</sub> O		0.0					<2.0%
SO <sub>2</sub>		0.1					<2.0%
HCI		0.1					<2.0%
HF			0.6				<2.0%
NH <sub>3</sub>			0.7				<2.0%
H₂O		0.0					<2.0%
CO <sub>2</sub>		0.0					<2.0%
H₂CO		0.2					<2.0%
CH₄		0.1					<2.0%
TOC		0.0					<2.0%







	Test	Resul	Results expressed as % of the			Other results	MCERTS
		<0.5	certificat <1	tion range <2	<del>=</del> <5		specification
Repeatability stareference point	andard deviation at						
O <sub>2</sub>		0.05					<0.2%
CO		0.1					<2.0%
NO		0.1					<2.0%
NO <sub>2</sub>				1.4			<2.0%
N <sub>2</sub> O		0.0					<2.0%
SO <sub>2</sub>		0.5					<2.0%
HCI		0.5					<2.0%
HF			0.6				<2.0%
NH <sub>3</sub>			0.8				<2.0%
H₂O		0.3					<2.0%
CO <sub>2</sub>		0.1					<2.0%
H₂CO		0.3					<2.0%
CH₄		0.1					<2.0%
TOC		0.1					<2.0%
Lack-of-fit							
O <sub>2</sub>	(0-25%Vol)	0.05					<0.2%
CO	(0-75mg/m <sup>3</sup> )	0.27					<2.0%
CO	(0-300 mg/m <sup>3</sup> )	0.33					<2.0%
CO	(0-4000 mg/m <sup>3</sup> )	-0.38					<2.0%
NO	(0-150 mg/m <sup>3</sup> )	-0.27					<2.0%
NO	(0-400 mg/m <sup>3</sup> )	0.25					<2.0%
NO	(0-2000 mg/m <sup>3</sup> )	0.50					<2.0%
NO <sub>2</sub>	(0-80 mg/m <sup>3</sup> )			1.00			<2.0%
NO <sub>2</sub>	(0-600 mg/m <sup>3</sup> )		0.83				<2.0%
NO <sub>2</sub>	(0-1000 mg/m <sup>3</sup> )	0.10					<2.0%
N <sub>2</sub> O	(0-50 mg/m <sup>3</sup> )	0.34					<2.0%
N <sub>2</sub> O	(0-1000 mg/m <sup>3</sup> )	-0.25					<2.0%
SO <sub>2</sub>	(0-75 mg/m <sup>3</sup> )	0.48					<2.0%
SO <sub>2</sub>	(0-300 mg/m <sup>3</sup> )		-0.67				<2.0%







	Test	Resul	ts expres	sed as %	of the	Other results	MCERTS specification
		<0.5	<1	<2	<5		opcoca.ic.
SO <sub>2</sub>	(0-300 mg/m <sup>3</sup> )	-0.28					<2.0%
HCI	(0-15 mg/m <sup>3</sup> )		-0.65				<2.0%
HCI	(0-90 mg/m <sup>3</sup> )		0.67				<2.0%
HCI	(0-2000 mg/m <sup>3</sup> )	0.45					<2.0%
HF	$(0-3 \text{ mg/m}^3)$		0.93				<2.0%
HF	$(0-6 \text{ mg/m}^3)$			1.00			<2.0%
HF	(0-300 mg/m <sup>3</sup> )		-1.00				<2.0%
NH <sub>3</sub>	$(0-5 \text{ mg/m}^3)$		-1.00				<2.0%
NH <sub>3</sub>	(0-15 mg/m <sup>3</sup> )		-0.80				<2.0%
NH <sub>3</sub>	(0-230 mg/m <sup>3</sup> )		-0.87				<2.0%
H <sub>2</sub> O	(0-40%Vol)	-0.35					<2.0%
CO <sub>2</sub>	(0-30%VoI)	0.17					<2.0%
H₂CO	(0-20 mg/m <sup>3</sup> )	0.49					<2.0%
CH₄	(0-7.5 mg/m <sup>3</sup> )	-0.33					<2.0%
CH <sub>4</sub>	(0-200 mg/m <sup>3</sup> )	-0.50					<2.0%
TOC	(0-15 mg/m <sup>3</sup> )	-0.47					<2.0%
TOC	(0-30 mg/m <sup>3</sup> )	-0.67					<2.0%
TOC	(0-300 mg/m <sup>3</sup> )	0.33					<2.0%
TOC	(0-500 mg/m <sup>3</sup> )	0.08					<2.0%
Influence of amb	oient temperature zero 30°C)						
O <sub>2</sub>		0.03					<0.5%
co		-0.1					<5.0%
NO		-0.4					<5.0%
NO <sub>2</sub>		-0.3					<5.0%
N <sub>2</sub> O		0.3					<5.0%
SO <sub>2</sub>		0.5					<5.0%
HCI		-0.3					<5.0%
HF			-1.0				<5.0%
NH <sub>3</sub>				-1.6			<5.0%
H <sub>2</sub> O		-0.1					<5.0%







Test	Resul		sed as % ion range		Other results	MCERTS specification
	<0.5	<1	<2 <2	<5		оростоціот
CO <sub>2</sub>	0.0					<5.0%
H₂CO	0.5					<5.0%
CH <sub>4</sub>	0.4					<5.0%
TOC	0.4					<5.0%
Influence of ambient temperature span point (+5°C to +30°C)						
O <sub>2</sub>	-0.19					<0.5%
CO	-0.3					<5.0%
NO	-0.5					<5.0%
NO <sub>2</sub>				2.4		<5.0%
N <sub>2</sub> O			1.2			<5.0%
SO <sub>2</sub>	-0.5					<5.0%
HCI		0.9				<5.0%
HF				-2.3		<5.0%
NH <sub>3</sub>				-2.4		<5.0%
H <sub>2</sub> O	-0.5					<5.0%
CO <sub>2</sub>	-0.3					<5.0%
H₂CO		-1.0				<5.0%
CH <sub>4</sub>			-0.3			<5.0%
TOC	-0.9					<5.0%
Influence of ambient temperature zero point (+5°C to +45°C)						
O <sub>2</sub>	0.02					<0.5%
СО	0.1					<5.0%
NO	-0.2					<5.0%
NO <sub>2</sub>		0.8				<5.0%
N <sub>2</sub> O	-0.1					<5.0%
SO <sub>2</sub>	0.4					<5.0%
HCI	-0.5					<5.0%
HF		-0.7				<5.0%
NH <sub>3</sub>			-1.6			<5.0%







Test	Resul		sed as %		Other results	MCERTS specification
	<0.5	<1	<2	<5		'
H₂O	-0.2					<5.0%
CO <sub>2</sub>	0.0					<5.0%
H₂CO	0.4					<5.0%
CH₄		-0.7				<5.0%
TOC	0.4					<5.0%
Influence of ambient temperature span point (+5°C to +45°C)						
O <sub>2</sub>	-0.21					<0.5%
СО	0.2					<5.0%
NO	-0.4					<5.0%
NO <sub>2</sub>			-1.5			<5.0%
N₂O	-0.4					<5.0%
SO <sub>2</sub>			1.2			<5.0%
HCI		0.9				<5.0%
HF				-2.3		<5.0%
NH <sub>3</sub>			1.4			<5.0%
H₂O	0.4					<5.0%
CO <sub>2</sub>	0.5					<5.0%
H₂CO			1.2			<5.0%
CH₄		0.7				<5.0%
TOC	0.5					<5.0%
Influence of sample gas flow for extractive CEMS						
O <sub>2</sub>	-0.15					<0.2%
СО		-0.7				<2.0%
NO		-0.9				<2.0%
NO <sub>2</sub>			-1.4			<2.0%
N <sub>2</sub> O		-1.0				<2.0%
SO <sub>2</sub>			-1.5			<2.0%
HCI	0.5					<2.0%
HF		0.8				<2.0%







Test	Resul	ts expres	sed as %	of the	Other results	MCERTS specification
	<0.5	<1	<2	<5		op comeanon
NH <sub>3</sub>	-0.6					<2.0%
H₂O		0.9				<2.0%
CO <sub>2</sub>		-0.9				<2.0%
H₂CO		-1.0				<2.0%
CH₄		-0.7				<2.0%
TOC			-1.5			<2.0%
Influence of voltage variations at zero (196V to 253V)						<2.0%
O <sub>2</sub>	0.00					<0.2%
СО	0.1					<2.0%
NO	0.2					<2.0%
NO <sub>2</sub>	-0.3					<2.0%
N₂O	0.3					<2.0%
SO <sub>2</sub>	0.3					<2.0%
HCI	-0.5					<2.0%
HF		0.7				<2.0%
NH₃		0.6				<2.0%
H₂O	0.0					<2.0%
CO <sub>2</sub>	0.0					<2.0%
H₂CO		0.6				<2.0%
CH₄	-0.3					<2.0%
TOC	-0.1					<2.0%
Influence of voltage variations at reference (196V to 253V)						
O <sub>2</sub>	0.05					<0.2%
СО	0.2					<2.0%
NO	-0.2					<2.0%
NO <sub>2</sub>	0.3					<2.0%
N₂O	0.3					<2.0%
SO <sub>2</sub>		0.9				<2.0%







Test	Resul	ts expres	sed as %	of the	Other results	MCERTS specification
	<0.5	<1	<2	<5		,
HCI	0.5					<2.0%
HF		1.0				<2.0%
NH <sub>3</sub>		-1.0				<2.0%
H₂O	0.2					<2.0%
CO <sub>2</sub>	0.1					<2.0%
H₂CO	-0.3					<2.0%
CH₄	0.3					<2.0%
TOC	-0.1					<2.0%
Cross-sensitivity at zero with interferents: O <sub>2</sub> , H <sub>2</sub> O, CO, CO <sub>2</sub> , CH <sub>4</sub> , N <sub>2</sub> O, NO, NO <sub>2</sub> , NH <sub>3</sub> , SO <sub>2</sub> , HCl						
O <sub>2</sub>	0.0					<0.4%
СО	0.0					<4.0%
NO		-0.64				<4.0%
NO <sub>2</sub>		0.61				<4.0%
N₂O		0.70				<4.0%
SO <sub>2</sub>				2.33		<4.0%
HCI			1.67			<4.0%
HF			-2.00			<4.0%
NH <sub>3</sub>			-1.80			<4.0%
H₂O	0.0					<4.0%
CO <sub>2</sub>	0.0					<4.0%
H₂CO	-0.45					<4.0%
CH₄	0.0					<4.0%
TOC				3.07		<4.0%
Cross-sensitivity at reference with interferents: O <sub>2</sub> , H <sub>2</sub> O, CO, CO <sub>2</sub> , CH <sub>4</sub> , N <sub>2</sub> O, NO, NO <sub>2</sub> , NH <sub>3</sub> , SO <sub>2</sub> , HCl						
O <sub>2</sub>	0.37					<0.4%
СО			1.29			<4.0%
NO			-1.67			<4.0%
NO <sub>2</sub>				2.95		<4.0%







Test	Resul		sed as %		Other results	MCERTS specification
	<0.5	<1	<2	<5		•
N₂O			-1.34			<4.0%
SO <sub>2</sub>				3.88		<4.0%
HCI				-3.75		<4.0%
HF				3.46		<4.0%
NH <sub>3</sub>				-3.80		<4.0%
H <sub>2</sub> O				2.80		<4.0%
CO <sub>2</sub>			2.00			<4.0%
H₂CO			1.95			<4.0%
CH₄			1.20			<4.0%
TOC				-3.61		<4.0%
Response factors for TOC CEMS:						
Methane					1.02	0.9 to 1.2
Aliphatic hydrocarbons					0.90 — 1.05	0.9 to 1.1
Aromatic hydrocarbons					0.91 – 1.08	0.8 to 1.1
Dichloromethane					0.92 - 0.93	0.75 to 1.15
Aliphatic alcohols					0.70 - 0.85	0.7 to 1.0
Esters and ketones					0.77	0.7 to 1.0
Organic acids					0.54 - 0.60	0.5 to 1.0







Test	Results expressed as % of the		Other results	MCERTS		
	<0.5	certificat	ion range <2	<del>&gt;</del> <5		specification
Measurement uncertainty					Guidance - at least 25% below max permissible uncertainty	
O <sub>2</sub>					2.9%	<7.5% (10%)
CO (For an ELV of 50 mg/m <sup>3</sup> )					5.0%	<7.5% (10%)
NO (For an ELV of 98 mg/m <sup>3</sup> )					5.5%	<15% (20%)
NO <sub>2</sub> (For an ELV of 50 mg/m <sup>3</sup> )					9.6%	<15% (20%)
N₂O					3.6%	<15% (20%)
SO <sub>2</sub> (For an ELV of 50 mg/m <sup>3</sup> )					9.4%	<15% (20%)
HCI (For an ELV of 10 mg/m <sup>3</sup> )					8.6%	<30% (40%)
HF (For an ELV of 1 mg/m <sup>3</sup> )					18%	<30% (40%
NH <sub>3</sub> (For an ELV of 2 mg/m <sup>3</sup> )					17.3%	<30% (40%
H₂O					4.2%	<7.5% (10%)
CO <sub>2</sub>					3.1%	<7.5% (10%)
H₂CO					4.3%	<7.5% (10%)
CH <sub>4</sub> (For an ELV of 5 mg/m <sup>3</sup> )					5.2%	<22.5% (30%)
TOC (For an ELV of 10 mg/m <sup>3</sup> )					10.1%	<22.5% (30%)
Calibration function (field)						
O <sub>2</sub>					0.99	>0.90
СО					0.99	>0.90
NO					0.99	>0.90
NO <sub>2</sub>					0.99	>0.90
N₂O					0.99	>0.90
SO <sub>2</sub>					0.99	>0.90
HCI					0.99	>0.90
HF					0.99	>0.90
NH <sub>3</sub>					0.98	>0.90
H <sub>2</sub> O					0.97	>0.90
CO <sub>2</sub>					0.99	>0.90
H₂CO					0.99	>0.90
CH₄					0.99	>0.90
TOC					0.98	>0.90







Test	Results expressed as % of the certification range				Other results	MCERTS specification
	<0.5	<1	<2	<5		opcomodion
Response time (field)						
O <sub>2</sub>					46s	<200s
СО					178s	<200s
NO					132s	<200s
NO <sub>2</sub>					172s	<200s
N₂O					162s	<200s
SO <sub>2</sub>					172s	<200s
HCI					233s	<400s
HF					178s	<400s
NH <sub>3</sub>					168s	<400s
H₂O					151s	<200s
CO <sub>2</sub>					132s	<200s
H₂CO					138s	<200s
CH₄					178s	<200s
TOC					39s	<200s
Lack of fit (field)						
O <sub>2</sub>	-0.06					<0.2%
СО	0.24					<2.0%
NO	0.33					<2.0%
NO <sub>2</sub>	-0.49					<2.0%
N₂O		0.58				<2.0%
SO <sub>2</sub>	0.40					<2.0%
HCI			1.73			<2.0%
HF			1.42			<2.0%
NH <sub>3</sub>			-1.40			<2.0%
H₂O	-0.47					<2.0%
CO <sub>2</sub>			1.73			<2.0%
H₂CO	0.45					<2.0%
CH₄	0.35					<2.0%
TOC	-0.20					<2.0%







Test	Results expressed as % of the Other results certification range				MCERTS specification	
	<0.5	<1	<2	<5		оростоинот
Maintenance interval					Note 1 12 months	>8 days
Zero and Span drift requirement	manua interna to tes measu drift is EN141	is an op ally to the al validati st gases irement of possible 81 for Q	Clause 6.13 & 10.13			
	point of and specific control of the measure of the applying of the preservant.	evice is experience in point and and a atically me FID. Drawer of the point and a proper in the direct in the all validations.	Manufacturer shall provide a description of the technique to determine and compensate for zero and span drift.			
Change in zero point over maintenance interval						
O <sub>2</sub>	0.15					<0.2%
СО	-0.3					<3.0%
NO	0.2					<3.0%
NO <sub>2</sub>		1.0				<3.0%
N₂O	-0.4					<3.0%
SO <sub>2</sub>		-0.8				<3.0%
HCI		0.9				<3.0%
HF			1.1			<3.0%
NH <sub>3</sub>				-2.3		<3.0%
H <sub>2</sub> O	0.0					<3.0%
CO <sub>2</sub>	-0.1					<3.0%
H₂CO	0.5					<3.0%
CH₄			1.1			<3.0%
TOC			-1.9			<3.0%







Test		Results expressed as % of the certification range			Other results	MCERTS specification
	<0.5	<1	<2	<5		
Change in reference point over maintenance interval						
$O_2$	-0.18					<0.2%
CO			1.3			<3.0%
NO			1.3			<3.0%
NO <sub>2</sub>				2.6		<3.0%
$N_2O$			1.9			<3.0%
SO <sub>2</sub>				2.3		<3.0%
HCI				2.6		<3.0%
HF				-2.1		<3.0%
$NH_3$				-2.4		<3.0%
H₂O			-1.6			<3.0%
CO <sub>2</sub>		0.6				<3.0%
H <sub>2</sub> CO			-2.0			<3.0%
CH <sub>4</sub>			1.9			<3.0%
TOC				2.3		<3.0%
Availability					98.5%	>95% (>98% for O <sub>2</sub> )







Test	Results expressed as % of the certification range			Э	Other results	MCERTS specification
	<0.5	<1	<2	<5		
Reproducibility						
O <sub>2</sub>	0.01					<0.2%
СО		0.6				<3.3%
NO	0.3					<3.3%
NO <sub>2</sub>		0.9				<3.3%
N₂O	0.2					<3.3%
SO <sub>2</sub>			1.8			<3.3%
HCI	0.4					<3.3%
HF		0.7				<3.3%
NH₃		0.9				<3.3%
H₂O	0.0					<3.3%
CO <sub>2</sub>	0.2					<3.3%
H₂CO	0.4					<3.3%
CH <sub>4</sub>	0.4					<3.3%
TOC			1.1			<3.3%

Note 1: TheACF5000 has a maintenance interval of 12 months. The work detailed below has to be carried out at regular intervals, depending on local conditions. This includes regular visual inspections and checks of the test gas filter, gas conditioning system, sample gas line and inlets. During the maintenance interval, zero and span checks must be performed for all components measured with the FTIR analyser. Zero and Span checks for O<sub>2</sub> and TOC must also be performed. Refer to User Manual for this operation.







# **Description**

The ABB ACF5000 system is a hot/wet extractive multigas analyser using Fourier Transform Infrared (FTIR) analysis to measure several gaseous components (including water), a zirconia-sensor based monitoring system to measure oxygen, and a flame ionisation detector (FID) - to measure total content of organic carbon. The FID can be optionally integrated. An internal validation unit can be used as an alternative to test gases for QAL3 span checks of the FTIR measurement components.

The loss-free measurement of the lowest concentrations of water-soluble components is achieved by seamless heating of the system to 180°C - from the probe filter element to the analyzer. A low-maintenance electronically controlled air injector system conveys the sample gas from the chimney stack to the analyzers at constant pressure in order to avoid pressure dependencies, which could arise if an uncontrolled feed pump were used. An optional blow-back unit allows for uninterrupted measurements even in high-dust-loaded applications.

Analogue Output, PROFIBUS, Modbus or Ethernet offers unrivalled connectivity to PLC, Data Acquisition Handling Systems (DAHS) or DCS.

#### **General Notes**

- 1. This certificate is based upon the equipment tested. The Manufacturer is responsible for ensuring that on-going production complies with the standard(s) and performance criteria defined in this certificate. The manufacturer is required to maintain an approved quality management system controlling the manufacture of the certified product. Both the product and the quality management system shall be subject to regular surveillance according to 'Regulations Applicable to the Holders of CSA Group Testing UK Ltd Certificates'.
- 2. The design of the product certified is defined in the CSA Group Design Schedule '06 revised' for certificate No. Sira MC160309.
- 3. If a certified product is found not to comply, CSA Group should be notified immediately at the address shown on this certificate.
- 4. The certification marks that can be applied to the product or used in publicity material are defined in 'Regulations Applicable to the Holders of CSA Group Testing UK Ltd Certificates'.
- 5. This document remains the property of CSA Group and shall be returned when requested by CSA Group.